

Platform

0.76 m x 1.83 m low mount platform

Side entry with inward swing gate

Multiple function operation

Full proportional drive joystick control with integral thumb steer switch

Full proportional main boom and swing joystick control

Variable speed dial control for lower boom, telescope and platform rotate

Selectable creep speed on drive / lift and swing functions

1.24 m articulating jib

170 degree powered platform rotator

Platform console machine status light panel ¹

Load sensing system

AC power cable to platform

Power & Transmission

Perkins 404C-22 (37 kW) diesel engine

Engine distress warning /shut down system ²

Gull-wing turntable hoods

Swing-out engine tray

Spark arresting type muffler

Control ADE™ (Advanced Design Electronics) System

Hydrostatic drive transmission

Horn

Functional Equipment & Accessories

4 degree tilt alarm and indicator light

33/1550 x 16.5 superwide foam filled tyres

Lifting/tie down lugs

Hour meter

Ground control selector switch with key lock

Platform tool tray

12V-DC auxiliary power

Available Options

0.76 m x 1.22 m low mount platform

0.76 m x 1.52 m low mount platform

13 mm air line to platform

Four wheel drive

12 x 16.5 Rim protector foam filled lug tread tyres

12 x 16.5 foam filled non marking tyres

Semi-track package (includes floating idler system)

Oscillating front axle

On-board 2500W generator

SkyPower™ package 7,500 watt on-board generator

¹ Provides indicator lights at platform control console for system distress, low fuel, tilt light, and foot switch status.

² Low oil pressure and high coolant temperature alarms with shut-down enabled/disabled by analyser.

³ Available when integrated with the SkyPower™ package

⁴ Includes all-motion alarm and flashing amber beacon.

⁵ Includes platform mounted work lights and head & tail lights.

⁶ Includes console cover, boom wipers and cylinder bellows.

Available Options

SkyWelder™ package 250 amp welder in the platform ³

Tow package

All motion alarm

Alarm package ⁴

Light package ⁵

Head and tail lights

Flashing amber beacon

Plugs & Sockets

Hostile environment package ⁶

Catalytic purifier muffler

Soft Touch proximity system

Corner storage tray



JLG Industries Inc.
 Polaris Avenue 63
 2132 JH Hoofddorp
 The Netherlands
 Tel: +31 (0)23 565 5665
 Fax: +31 (0)23 557 2493
 e-mail address: europe@jlg.com
www.jlgeurope.com
 An Oshkosh Corporation Company

Printed in UK
 FORM No.: DS039-0308-100
 PART NO.: DS039-ENGLISH



450AJ

Platform height	13.72 m
Horizontal outreach	7.47 m
Up and over height	7.67 m
Swing (non continuous)	360°
Platform capacity – unrestricted	230 kg
Platform rotator (hydraulic)	170°
Jib – overall length	1.24 m
Jib - range of articulation	145° (+78°/ -67°)
A. Platform size	0.76 m x 1.83 m
B. Overall width	2.08 m
C. Tailswing (working condition)	Zero
D. Stowed height	2.25 m
E. Stowed length	6.53 m
F. Wheelbase	1.98 m
G. Ground clearance	0.36 m
Machine weight ¹	7,400 kg
Maximum ground bearing pressure	5.5 kg/cm ²
Drive Speed 2WD	5.6 km/h
Drive Speed 4WD	7.2 km/h
Gradeability 2WD	30%
Gradeability 4WD	45%
Tyres (foam filled)	33/1550 x 16.5
Axle oscillation ²	0.20 m
Turning radius – inside	1.73 m
Turning radius – outside	4.27 m
Diesel engine Perkins 404C-22	37 kW
Fuel tank capacity	62.5 L
Hydraulic system	130 L
Auxiliary power	12V DC

¹ Certain options or country standards may increase weight and/or dimensions.

² Optional on models 450A and 450AJ.

